

**DUMPSTER, 30 CUBIC YARD, STANDARD DUTY,
RECTANGULAR STYLE, OPEN TOP SPECIFICATIONS:**

LENGTH	22' LONG
WALL HEIGHT	60"
FLOOR:	7 GAUGE
CROSSMEMBERS:	3", 3.5# STRUCTURAL CHANNEL ON 24" CENTERS
WALLS:	12 GAUGE
RIBS:	4" x 3" x 12 GAUGE FORMED CHANNEL
TOP RAILS:	4" x 3" x 11 GAUGE STRUCTURAL TUBING
DOOR SHEET:	12 GAUGE
DOOR FRAME:	5" x 3" x 10 GAUGE FORMED CHANNEL
DOOR CLOSURE:	LEVER TYPE
ROLLERS:	8" DIA x 10" LONG AT REAR, 8" LONG AT FRONT
MAIN RAILS:	6" x 2" x 3/16" STRUCTURAL TUBING
RAIL EXTENSION:	1 3/8" PLATE
PULL HOOK:	1 1/4" PLATE, 36,000 PSI MINIMUM YIELD STRENGTH
HOOK PLATE:	3/4" PLATE

WELDS: WALLS WELDED CONTINUOUSLY TO FLOOR OUTSIDE, SKIP WELDED INSIDE. ALL OTHER SEAMS ARE CONTINUOUS INSIDE, SKIPPED OUTSIDE.

FINISH: PRIMED INSIDE AND OUT, EXTERIOR COATED WITH ALKYD ENAMEL.

**DUMPSTER, 15 CUBIC YARD, STANDARD DUTY,
RECTANGULAR STYLE, OPEN TOP SPECIFICATIONS:**

LENGTH	14' LONG
WALL HEIGHT	48"
FLOOR:	7 GAUGE
CROSSMEMBERS:	3", 3.5# STRUCTURAL CHANNEL ON 24" CENTERS
WALLS:	12 GAUGE
RIBS:	4" x 3" x 11 GAUGE FORMED CHANNEL
TOP RAILS:	4" x 3" x 11 GAUGE STRUCTURAL TUBING
DOOR SHEET:	12 GAUGE
DOOR FRAME:	5" x 3" x 10 GAUGE FORMED CHANNEL
DOOR CLOSURE:	LEVER TYPE
ROLLERS:	8" DIA x 10" LONG AT REAR, 8" LONG AT FRONT
MAIN RAILS:	6" x 2" x 3/16" STRUCTURAL TUBING
RAIL EXTENSION:	1 3/8" PLATE
PULL HOOK:	1 1/4" PLATE, 36,000 PSI MINIMUM YIELD STRENGTH
HOOK PLATE:	3/4" PLATE

WELDS: WALLS WELDED CONTINUOUSLY TO FLOOR OUTSIDE, SKIP WELDED INSIDE. ALL OTHER SEAMS ARE CONTINUOUS INSIDE, SKIPPED OUTSIDE.

FINISH: PRIMED INSIDE AND OUT, EXTERIOR COATED WITH ALKYD ENAMEL.